#### R91

THREE-PHASE ONLINE UPS 415/240VAC, 400/230VAC · The R91 UPS is available in or 380/220VAC

18kW of efficient and reliable power in just 5U of rack space



140& 140i ULTRA-SLIM SURGE PDU 120V or 230V



Protect AV, digital signage, kiosks, and POS from transients with ultra-slim J40 PDU

• Up to 99% efficiency

in ECO mode and 94%

efficiency in online mode

many custom configurations

including parallel tie with up

to 4 modules, 480V input,

maintenance bypass, and

· Slim (1.2") J40 mounts behind displays and in tight spaces · Over voltage and over temperature MOV protection · Power reset button allows manual cycling of power

XBDM

BYPASS DISTRIBUTION 15, 20, 30, 63A

Repair or replace your UPS without power interruption by manually transferring critical loads from UPS power to utility power using the XBDM.

replacement and reduces costly downtimes · Offers surge protection during UPS and utility mode · Plug/receptacle and hardwired models available · The ideal solution to reduce costly downtime; read the white paper at www.xpcc.com/whitepaper

· Simplifies UPS repair or



XPDU

POWER DISTRIBUTION 15, 20, 30, 50A

Rack power distribution solutions designed to meet the needs of any data center or wiring closet.

· XPDUs provide up to 24 receptacles for power distribution · Switched PDU provides remote on/off control of receptacles · Transformer PDU provides 208-120VAC step down · Multiple input configurations available · Wall, rack, and floor mount options available



## J40SP ULTRA-SLIM SURGE PDU

120V · Reboot devices via remote power switch · Over voltage and over temperature MOV protection · Slim (1.2") J40SP mounts behind displays and in tight spaces

Protect AV equipment, Kiosks and other remote devices with ultra-slim J40SP surge PDU



XC

COOLING FOR

Protect critical electronics from high temperature environments.



· Ideal for networks, communications, and

server rooms · Primary, backup, or after hours cooling

Uses earth friendly R410A refrigerant

· 13,200, 21,000, & 29.000 BTU/H models

## POWER PROTECTION FOR MISSION CRITICAL APPLICATIONS

Xtreme Power manufactures UPS, power distribution units, and portable cooling products for a global network of OEMs and

Configure your UPS applications

www.xpcc.com/selector

For the most up to date flyers and documentation, please visit our website at: www.xpcc.com

## XTREME POWER CONVERSION CRITICAL POWER SOLUTIONS





All rights reserved. ALL.01U (10/18/17)



13,200-29,000 BTU/H

© 2017 Xtreme Power Conversion Corporation

## 160 & 160i

350VA LITHIUM-ION UPS 120V or 230V



XST 400VA-800VA STANDBY UPS

120V

Safeguard your computer from power outages with dependable power

protection.



S70 500VA-2000VA LINE INTERACTIVE UPS 120V



Equip your office with reliable battery backup

life

Auto restart

monitors UPS vitals

· Wide operating voltage

means longer battery

· Automatic Voltage

Regulation (AVR)

and protection from power outages. · Smart LCD display



· Ideal for home or small office, desktop computers, routers, switches, and telecom closets

Protect AV and automa-

with ultra-slim J60 UPS.

· Slim and light weight

(1.2" and 3.4 lbs) J60

provide protection for

up to 8 years and 2000

Ideal for digital signage,

PLCs, Kiosks, gaming

machines and POS

panel displays

discharges

· Lithium batteries

mounts easily behind flat

surges and power outages

tion electronics from

V80 700VA-2000VA

LINE INTERACTIVE UPS 120V

Value series line interactive power protection for servers and network equiptment.



Pure sine wave output

· Automatic voltage

· Up to 96% efficiency

· Rack, tower and wall

· 0.9 output power factor

for high density loads

· 99% efficiency in ECO

· Rack, tower and wall

· Extended battery packs

available for 1500VA-

mode

mounting

5kVA models

regulation (AVR)

mounting

P80 & P80g 800VA-5kVA

LINE INTERACTIVE UPS 120V or 208/230V

Advanced pure sine wave line interactive power protection for servers and network equipment.



T91 700VA-3000VA **ONLINE TOWER UPS** 120V or 208/230V



Unity power factor tower UPS provides high density online power protection for unstable power conditions.

> · Features unity output power factor to support up to 43% more critical loads than typical UPS · Fast recharge time: up to 95% in just 3 hours Extended battery packs available

### TX90 1000VA-5000VA ISOLATED ONLINE UPS 120V or 230V

P90 & P90g

1000VA-3000VA

120V or 208/230V

Slim form factor UPS

continuous power to

IT equipment during

power disturbances.

P91

battery.

5kVA-10kVA

ONLINE UPS

208/230V or 208/120V

More power in less space

with lead acid or lithium ion

delivers clean and

ONLINE UPS



· High output power factor for high density loads • 98% efficiency in ECO mode · P90g-1000 & P90c-1000 with just 1U rack space

## · P90L with high capacity charger available for long runtime applications



**NEW** 

n 2018

· Unity output power factor for high density loads Optional 2U PDU with isolation transformer provides 120V output · Tower, 2-post, and 4-post rack mounting configurations available



#### Online UPS with isolation transformer for complete power protection.

· Supports worldwide applications. TX90 accepts input power from 88-288VAC and 40-70Hz Galvanic isolation transformer isolates loads from common mode noise

M90 & M90L

15kVA-60kVA MODULAR ONLINE UPS 208/120VAC 3 PHASE

Mission Critical availability while reducing costs with scalable, modular M90 UPS.



· When power and runtime requirements change M90 modularity makes it easy to add modules and increase capacity Choose 15kVA or 20kVA power modules · Up to 98% ECO mode or 94% online efficiency, **Energy Star Certified** 

Increase efficiency and

single-phase UPS.

operation

to 8 hours

problems.

noise

reduce power consumption

with this powerful online

· 0.9 output power factor

for high density loads

· Up to four units can be

capacity or redundant

· Extended battery packs available for runtimes up

Isolated online UPS

all 10 common power

provides protection from

paralleled for additional

6kVA, 10kVA ONLINE UPS



# **ISOLATED ONLINE UPS**



· 0.9 output power factor for high density loads • Up to four units can be paralleled for additional capacity or redundant operation · Complete galvanic isolation transformer isolates common mode

## T90 6 & 10kVA 208V or 230V



## TX90 6 & 10kVA 6kVA, 10kVA 240/120V or 208/120V



For detailed specs on all our products, visit www.xpcc.com

